

Ⓐ Unless otherwise specificed upon order, Customer Required Clearance is automatically set to 2 mm by Pulseroller USA Order Entry System

INCLUDED ITEMS		
ITEM	DESCRIPTION	QTY
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZxAQ	
TUBE DIA	48.6 mm
INTERLOCK	NONE - PLAIN STRAIGHT
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST (S) OR M8 (M)

xxx = RL in mm
xx = Speed Code

PULSEROLLER
WEB: WWW.PULSEROLLER.COM
SUPPORT: SUPPORT@PULSEROLLER.COM
SALES: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET
D	24-JAN-2023	COMBINED JST & AI TO ONE DWG, CHANGED DWG NUMBER

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.

DATE: 21-MAR-2014
DESIGNED BY:
CHECKED BY:
SCALE: NONE
SHEET: 1 OF 1

TITLE: STANDARD 48 DIA PLAIN STRAIGHT
PART NUMBER PR-AD-48-xxx-xxZxAQ

FOR: SENERGY MOTOR ROLLER
PULSEROLLER STANDARDS

DWG. NO: PR-AD-48-xxx-xxZxAQ
REV: D