



INCLUDED ITEMS		
ITEM	DESCRIPTION	QTY
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZxFQ	
TUBE DIA	48.6 mm
INTERLOCK	ROUND GROOVE PULLEY
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST (S) OR M8 (M)

Unless otherwise specified upon order, Customer
 (A) Required Clearance is automatically set to 2 mm by
 Pulseroller USA Order Entry System

xxx = RL in mm
 xx = Speed Code



PULSEROLLER
 WEB: WWW.PULSEROLLER.COM
 SUPPORT: SUPPORT@PULSEROLLER.COM
 SALES: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION
E	24-JAN-2023	COMBINED JST & AI TO SAME DWG. UPDATED DWG NUMBER
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	10-MAY-2021	CORRECTED LENGTH FORMULA
D	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET

REV.	DATE	DESCRIPTION
E	21-MAR-2014	THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.

TITLE:	STANDARD 48 DIA ROUND GROOVE PULLEY
FOR:	SENERGY MOTOR ROLLER PULSEROLLER STANDARDS
DWG. NO.:	PR-AD-48-xxx-xxZxFQ